



CONCEPT

The DMW300 is the chameleon of program sources for commercial sound systems, and can work as a stand-alone media player, as a network media player playing files from the network via UPnP, as an internet radio and also as a terrestrial FM radio receiver with RDS readout. Connections to a local network can either be made via LAN or via WiFi if an optional WiFi dongle is inserted into the rear USB socket provided for this purpose. Including connection to the comprehensive Skytune server portal, the DMW300 offers access to thousands of well categorized internet radio stations from around the world, which makes it one of the most worry-free background

music sources available, with the right tunes for every environment. Great emphasis has been put on the ease of operation, with all programming and set-up functions being not accessible to the common user, at the same time with direct access to all regularly used functions, thus removing complexity from daily use and making a once done setup permanent. The integrated jingle player allows to insert up to 3 advertisements, promotional messages or other announcements automatically with scheduled replay into the music program. An included IR remote control further enhances the comfort of operation of this versatile unit.

FEATURES

- Media player with stand-alone mode and LAN replay via UPnP, folder and playlist support
- Playable file formats MP3, WMA, FLAC, AAC, WAV and OGG
- Play mode for local or UPnP file replay settable to sequential or shuffle
- Repeat mode for local or UPnP file replay settable to none – one – all
- MP3 ID3 tag readout on display
- Internet Radio receiver with access to Skytune server portal with thousand of categorized stations
- Embedded web server for internet radio station preset editing
- Optional Wifi connectivity via external WiFi dongle (not included)
- Terrestrial FM receiver with RDS readout and auto-scanning for station presets
- 10 direct access buttons with programmable station assignment
- Built-in Jingle Player to insert up to 3 jingles into running program material with scheduled replay
- 128x64 pixels backlit graphics LCD display
- IR remote control included
- Balanced (XLR) and unbalanced (RCA) output
- Output level setting on rear panel
- Internal symmetrical power supply for excellent dynamics
- AC mains voltage selector switch 115/230V
- All-metal case with brushed aluminum front panel
- CE/ROHS compliant

TECHNICAL DATA

AC IN (EU setting).....AC220-250V~ 50Hz
AC IN (US version).....AC110-120V~ 60Hz
Power consumption.....max. 12W

Dimensions.....W483(427)xH44.5xD183.5mm
(parentheses = without rack ears)
Weight.....2.2 kg



Rear View