



TECHNICAL DATA

Signal/Noise...>82dBu (unwgted 22Hz-22KHz)
 Crosstalk Damping.....>65dB (Line)
 THD.....<0.05% (Line)
 Frequency response.....20Hz – 20 kHz
 AC IN115V/230~ 50/60Hz
 Power consumption.....max. 15W
 Dimensions.....W483xH88.0xD80.0mm
 Weight.....2.3kg

LOGISTICS DATA

Order Number.....2003501
 Single unit EAN-13.....5060502920393
 Single Carton size.....525x135x265mm
 Single Carton gross weight.....2.9kg
 Units per master carton.....2
 Master carton size.....545x300x280mm
 Master carton gross weight.....6.7kg

CONCEPT

The PSM-2220 Stereo Production Mixer packs all essential features for venues which require music replay with vocal announcements in the outmost compact package. With only 88mm height and nearly the same depth, the PSM-2220 is predestined for applications where space is a major concern, such as compact mobile systems or hospitality music systems which share the space with a bar or reception counter. Despite its compactness, it sports all the features which a host or DJ would expect – 6 stereo inputs with individual EQ, two microphone inputs with EQ and auto-talkover, and two separate master outputs. Any sound engineer, DJ or host will instantly recognize the versatility of this unit with no compromises made in usability and quality.

FEATURES

- 2 triple-source stereo inputs (Phono (Line)/Line/Aux) with gain control, 3-band Kill-EQ (+12/-26dB) and 5-LED level meter
- Utility input switchable between balanced stereo input (FOH input) and front panel 3.5mm stereo TRS input
- 45mm smooth dual-rail input channel faders
- 2x Mic inputs (1x front-panel Combo + rear-panel TRS, 1x rear-panel TRS) with 3-Band EQ, volume control and "on air" switch
- Adjustable auto talk-over for automatic music level reduction when microphone is used
- 45mm smooth dual-rail crossfader with on/off switch
- 2 Independent balanced stereo main outputs with rear-side maximum volume adjustment
- Mono switch and switchable HP filter for both outputs
- 10-LED level meter assignable to either main output
- PFL section with PFL/Main mix control and Blend/Split option
- Unbalanced record output
- Ultra-compact 95mm depth to minimize space consumption in L-Racks
- All switches with LED status indicator
- Internal wide-voltage swing linear power supply for excellent audio dynamics
- Full metal case with detachable rack ears
- AC mains voltage selector switch 115/230V
- CE/ROHS compliant

